

Index Measuring Device BECO® LiquiControl₂



Fully-automatic Device for Determining Filterability

BECO LiquiControl₂ index measuring device from Eaton's Begerow Product Line primarily determines the filterability of any beverage or ready-to-bottle liquid. Prior to membrane filtration, a sample is filtered under defined and reproducible conditions (constant pressure) through a reference membrane.

Depending on the sample quantity, the filterability of the medium is considered "good" if a defined sample volume is achieved. If the defined volume is not obtained, further measurements for the improvement of filterability become necessary.

If a single sheet lab filter (e.g., BECO INTGRA® LAB 60) is connected to the device instead of the filter carrier, the ideal filter sheet can be determined as well.

A variable pressure setting allows for different depth filter sheets to be considered.



Advantages

- **Ideal assessment** of the filterability and the quality of the filtrate
- **Longer total service life** of the membrane filter cartridges for pre-filtration and targeted determination of the regeneration intervals.
- **Reduction of downtime** during filling due to perfect pre-filtration
- **Enables optimum choice** of cartridge filter systems due to pilot tests
- **Polluting load analysis** of service media (rinse water, steam condensate)
- **Easy handling and cleaning** of the device
- **Variable filtration pressure**
- **High flexibility** due to a separate container for liquid to be filtered
- **Display of all measured data from archive**
- **Ethernet interface** for data download

Filterable Media

- Wine/sparkling wine
- Water/mineral water
- Juice
- Beer from pressure containers
- Service media

Display Values

During measurement:

Current filtrate volume in ml

Current pressure of sample in mbar

Flow rate in ml/min

Current temperature of medium

After measurement:

Flow rate with 1 liter filtrate volume in ml/min

Flow rate with 2 liter filtrate volume in ml/min

Flow rate with 3 liter filtrate volume in ml/min

Flow rate with 4 liter filtrate volume in ml/min

Flow rate with 5 liter filtrate volume in ml/min

Entire filtrate volume in ml

Technical Data

Max. volume:	1.43 gal (5.4 l)
Operating pressure:	0 – 43.5 psi (0 – 300 kPa, 0 – 3 bar)
Membrane diameter:	1.85 in (47 mm)
Membrane, pore size:	0.45 µm; 0.65 µm
Max. temperature of medium:	176 °F (80 °C)
Max. ambient temperature:	33.8 – 122 °F (1 – 50 °C)
Weight:	37.5 lb (17 kg)
Dimensions (L x W x H):	Measuring device: 13.8 x 11.8 x 17.7 in (350 x 300 x 450 mm) Container: Ø 7.9 in, height: 13.8 in (Ø 200 mm, H: 350 mm)
Display:	Micro-Panel 3,5" Color-Touch-Display

Materials:

Measuring device, filter carrier:	Stainless steel AISI 304/AISI 316L
Container:	Stainless steel AISI 304
Product contacting parts:	Stainless steel AISI 304/AISI 316L, PA

North America - HQ

44 Apple Street,
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America Only)
Voice: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Voice: +49 2486 809-0

Internormen Product Line

Friedensstraße 41
68804 Altlußheim, Germany
Voice: +49 6205 2094-0

Begerow Product Line

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Voice: +49 6704 204-0

Brazil

Av. Julia Gaioli, 474 - Bonsucesso
07251-500 - Guarulhos
Brazil
Voice: +55 11 2465 8822

China

No. 7 Lane 280 Linhong Road,
Changning District,
Shanghai 200335, China
Voice: +86 21 5200 0422

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Voice: +65 6825 1668

Connections

Voltage/frequency:	230 V/50 Hz 110 V/60 Hz
Protection class:	IP54
Inlet connection:	Ø 1.14 in (Ø 29 mm)

Accessories

Article-number	Description	Packing unit
BJTI2000	BECO LiquiControl ₂ index measuring device including container for liquid to be filtered	1
BJTI2B01	Additional container for liquid to be filtered, 1.43 gal (5.4 l)	1
BFI45047	Membrane 0.45 µm	100
BFI65047	Membrane 0.65 µm	100

HS Customs Tariff: 8421 99 00

For more information, please e-mail us at filtration@eaton.com or visit us online at eaton.com/filtration for a complete list of Eaton's filtration products.

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local Eaton office to determine availability.

© 2013 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.